

Status of the POAM III Algorithm and Data Set

POAM Science Team:

R. Bevilacqua (PI,NRL)

J. Lumpe (CPI)

C. Randall (CU)

D. Allen (NRL)

J. Hornstein (NRL)

C. Benson (NRL)

R. Salawitch (JPL)

G. Manney (JPL)

A. Strawa (NARC)

C. Brogniez (Lille)

B. Connor (NIWA)

S. Massie (NCAR)

K. Hoppel (NRL)

M. Fromm (CPI)

G. Nedoluha (NRL)

E. Shettle (NRL)

A. Prados (NRL)

J. Alfred (CPI)

M. Santee (JPL)

D. Rusch (CU)

K. Drdla (NARC)

H. Steele (CSUN)

K. Kreher (NIWA)

L. Pan (NCAR)



POAM is a 9-channel visible/near infrared photometer for making measurements of stratospheric constituents using solar occultation techniques.

- ■POAM II was launched on 26 Sep., 1993 on the French SPOT 3 spacecraft into a polar sun synchronous orbit (98.7° inclination, 10:30 equatorial crossing) and operated until the satellite failed in Nov. 1996.
- The POAM II measurement complement includes: Ozone (10-60 km) Aerosol Extinction (10-30) Nitrogen Dioxide (20-40 km)
- POAM III

 Designed of additional A Quadried In

 TREX SENTERPRISES


 Sen Dispo. Colleges

 POAM III was launched on SPOT 4 (orbit identical to that of POAM II) on 23 March
- 1998. The instrument is currently operational.

 ■The POAM III measurements:
 Ozone (5-60 km)

Aerosol Extinction (5-30 km)
Nitrogen Dioxide (20-45 km)
Water Vapor (5-45 km)
Atmospheric Density (30-60 km)





- POAM II and III measurement coverage is identical, and are both annually periodic.
- The POAM measurements provide continuous coverage of the polar regions.
- POAM is complementary to SAGE III, which measures to higher latitudes in the north, but lower latitudes in the south.
- The POAM measurement coverage is nearly identical to that of ILAS I and II



POAM Measurement Channels

Channel	Center wavelength (nm)		Bandwidth (nm)		Primary Purpose	
	POAM II	POAM III	POAM II	POAM III	POAM II	POAM III
1	352	354	4.5	10	Rayleigh	Rayleigh
2	442	440	2	2	NO ₂ off/Aer	NO ₂ on
3	448	442	2	2	NO ₂ on	NO ₂ off/Aer
4	601	603	14	18	O ₃	O ₃
5	761	761	2	2	O ₂ on	O ₂ on
6	781	779	17	10	O ₂ off / Aer	O ₂ off/Aer
7	921	922	2	2.5	H ₂ O off/Aer	H ₂ O off/Aer
8	936	936	2	2.5	H ₂ O on	H ₂ O on
9	1060	1018	11	12	Aerosol	Aerosol

POAM III Version 3 algorithm (current operational algorithm)


- ☐ Retrievals done on a 1-km altitude grid
- ☐ Three step approach:
 - 1. Computation of total slant optical depths
 - 2. Spectral inversion:
 - ➤ Simultaneous retrieval of O₃, O₂, NO₂, H₂O, and aerosol slant path column densities at each altitude grid point.
 - > Assume the following parameterization for the λ dependence of the aerosol optical depth:

$$\ln \delta_{aer}(\lambda) = \mu_o + \mu_1 \ln \lambda + \mu_2 \ln^2 \lambda$$

- 3. Limb inversion:
 - Converts slant path column densities and aerosol optical depths to gas concentration and aerosol extinction profiles.




Retrieval Error Analysis





Retrieval Vertical Resolution




Over most of the retrieval range, the POAM constituent retrieval vertical resolution is ~ 1-2 km.
Degradation in resolution at the highest and lowest altitudes is the result of

decreasing SNR




Sunspot Artifact Errors




 Sunspots can cause a decrease in signal well above the noise level.

- ☐ Because the sun is scanned above the atmosphere in each event, with accurate determination of the tracking offset, the sunspot effect will be normalized out.
- ☐ The effect of small, random pointing errors is magnified by sunspots.






Empirical error bars due to sunspot artifacts.




- •Errors for sunspot indices of 1-8
- Range of profiles



Empirical error bars due to sunspot artifacts.







Empirical Errors due to Aerosol Contamination

- Errors for aerosol extinction of 10⁻⁶ 10⁻² km⁻¹
- Range of retrieved values
- PSC extinction range

- NO₂ and H₂O can be impacted by high aerosol loading typical of PSCs.
- O_3 impact is minimal.

POAM Validation Summary

Ozone

Lumpe *et al.*, in press at JGR, 2002. Prados *et al.*, in press at JGR, 2002. Randall *et al.*, in press at JGR, 2003.

Aerosols

Randall et al., JGR 106, 27525-27536, 2001.


NO₂

Randall et al., JGR 107, 2001JD001520, 2002.

• H₂O

Nedoluha *et al.*, *JGR*, 107, 2001JD001184, 2002. Bevilacqua *et al.*, in preparation.


Ozone Validation: Satellite and Sonde Comparisons






Ozone Validation: MOZAIC Comparisons


POAM/MOZAIC Coincidences






From Prados et al., in press at JGR, 2002

Aerosol Validation: SAGE II Extinction Comparisons



NO₂ Validation: HALOE and SOLVE Comparisons





480 X POAM III

Potential Temperatue (K)

440

420

400

380

360

340


ER-2/JPI

H₂O (ppm)


ER-2/HU

Polar Ozone and Aerosol Measurement (POAM) Program


H₂O Validation: HALOE and SOLVE Comparisons



POAM/ HALOE Summary




H₂O Validation: MOZAIC Comparisons



POAM temperature retrieval

- ☐ Uses O₂ densities retrieved from Rayleigh scattering (not O₂ A band)
- □ Not operational in Ver. 3

POAM/HALOE & POAM/UKMO
Temperature Comparison Study





POAM III Validation Summary

Ozone H₂O

Range: 5-60 km

Resolution: 1 km

Random Error: 5%

SR/SS Bias: SS > SR, 5%

(30-60 km)

Validation: $\pm 5\%$, Z > 12 km

Range: 5-50 km

Resolution: 1-3 km

Random Error: 5%

SR/SS Bias: SS > SR, 5%

(20-50 km)

Validation: 5% high bias

NO₂

Range: 20-45 km

Resolution: 1.5-3 km

Random Error: 5%

SR/SS Bias: Insignificant

Validation: $\pm 5-10\%$

Diurnal correction

Aerosols

Range: 5-30 km

Resolution: 1 km

Random Error: 10-20%

SR/SS Bias: SR < SS

SR > SS

Validation: ±30%, background

Sunspots $H_2O > NO_2 > O_3$

 $\frac{\mathsf{Aerosols}}{\mathsf{H}_2\mathsf{O} > \mathsf{NO}_2 > \mathsf{O}_3}$


On to Version 4: Objectives

- Improved pointing information in transmission algorithms.
- New aerosol parameterization in spectral inversion.
- Investigate modifying the constraints in the retrieval.
- Operational temperature retrieval.
- Incorporation of oxygen A band (?).




POAM pointing issues:

- POAM FOV is wider than the width of the sun
- POAM tracks on the sun center of brightness.



Instrument tracking on the solar disk.



Altitude regimes currently used in Ver. 3 algorithm

Aerosol Parameterization

Version 3 nonlinear parameterization:

$$\ln \delta_{aer}(\lambda) = \mu_o + \mu_1 \ln \lambda + \mu_2 \ln^2 \lambda$$

Possible alternate linear parameterizations:


$$\delta_{aer}(\lambda) = \mu_o + \mu_1 \ln(\lambda/\lambda_9) + \mu_2 \ln^2(\lambda/\lambda_9)$$

$$= \mu_o + \mu_1 \lambda^{-1} + \mu_2 \lambda^{-4}$$

$$= \sum_i \mu_i T_i(\lambda)$$



Example of effect of tighter constraints on H₂O retrievals during SOLVE.





Science Highlights

■ Polar Stratospheric Clouds

▶ Unique PSC data set in the 1990's

■ Ozone Depletion

- **▶** Contributed to NASA SOLVE I and II missions
- Measures Arctic ozone variations.
- ▶ Formation and evolution of Antarctic ozone hole.
- **Dehydration of the Antarctic vortex.**

■ Upper Troposphere/Lower Stratosphere

- ▶ First evidence that boreal forest fire smoke can reach the lower stratosphere.
- **▶** Diagnostic of UT/LS transport via water vapor and ozone morphology.

■ Mesosphere/Stratosphere Coupling


- ▶ Detected stratospheric ozone loss after transport of enhanced odd nitrogen across the stratopause.
- ▶ First satellite measurements of PMCs in extinction -- possible climate change implications.


Important science issues which can be addressed by solar occultation measurements:

- ☐ Ozone Loss
- ☐ PSC microphysics: Strawa et al. (2003) PSC type discrimination algorithm
- ☐ Dehydration of the Antarctic polar stratosphere
- ☐ UT/LS issues




Dehydration of the Antarctic Vortex






Dehydration of the Antarctic Vortex




Dehydration of the Antarctic Vortex: measurement/model






POAM ozone and water vapor in the UT/LS






POAM ozone and water vapor in the UT/LS

Troposphere to Stratosphere Exchange





Summary:

- □ POAM III was launched in March 1998, and is currently operational. It is the successor to POAM II which operated from Oct. 1993 to Nov. 1996.
- ☐ The current retrieval version is Ver. 3, which has now been validated.
- □ POAM II data is archived at the Langley DAAC, and POAM III data is publicly available (http://www.cpi.com/products/poam)
- □ POAM validation and science publication record to date (since 1995):

Refereed journals: 60 publications, 5 in press, and 1 submitted. Papers in conference proceedings: 20 Presentations: more than 150.